

Desoldering/Rework

Handy Desoldering Tool

HAKOFR-300 DESOLDERING TOOL



Handy Desoldering Tool

Four new features that increase workability and efficiency

Quick Change Nozzle System provides speed and safety.





3 Calculated weight balance

Motor, pump, and temperature control circuit are optimally positioned within the body to ensure good balance when holding the gun.

The new Quick Change Nozzle System allows for a safer and simpler method to quickly remove nozzles for cleaning or replacement, even when the unit is hot.



Well-balanced
Ergonomic design for operators' comfort

Motor

Temperature
Pump

Dial control for easy temperature selection

The dial integrated into the handle makes it easy to adjust the temperature setting without the use of additional tools.

Setting 1	350°C	Setting 2	400°C
Setting 3	450°C	Setting 4	500°C

LED indicators let you easily see when the heater is active and idling at your temperature setting.


Dial for temperature control



Features LED lamp that indicates heater's activity

Integrated power switch

Locating the power switch on the handle makes it possible to turn the tool on and off with ease and



does away with the hassle of having to remove the plug when you want to turn off the tool.



FR-300

Simple iron holder included

Includes simple iron holder that prevents burns and accidents from hot parts.

Packing List



HAKKO FR-300 Handy Desoldering Tool

CONTENTS: Cleaning pin for ϕ 1.5 mm nozzes. Cleaning pin for hearing con, Ceramic paper filter (large x2), Simple con holder. Aumnum pre-lier, Nozze wrench, Instruction manual



Part No.	Part name
C1100	Iron holder



Part No.	Part name	Nozzle dimensions
B1302	Cleaning drill	For φ0.8 mm
B1303		For φ1.0 mm
B1304		For φ1.3 mm
B1305		For φ1.6 mm
B1085		For heating element
B1086		For φ0.8 mm nozzle
B1087	Cleaning pin	For \$1.0 mm nozzle
B1088		For φ1.3 mm nozzle
B1089		For \$1.6 mm nozzle

HEAD OFFICE

E-mail:info@hakko.com.hk

*	B1087	is	included	in	FR-300.

Replacement Parts				
Part No.	Part name			
A5000 Heating element 100-120 V				
A5001 Heating element 220-240 V				
A1217	7 Front holder			
B5014 Element cover				
B5016 Pre-filter (ALUM) set of 5				
B5017	Filter pipe			
A1033	Ceramic paper filter (L) set of 10			

Replacement Nozzles (Unit: mm)					
Part No.	Shape	φA (mm)	φB (mm)		
N50-01	фВ ФА	0.8	2.0		
N50-02		1.0	2.0		
N50-03		0.8	2.5		
N50-04	фВ Б	1.0	2.5		
N50-05		1.3	3.0		
N50-06		1.6	3.0		

Specifications				
Model No.	FR-300			
Power consumption	100 V 98 W (50/60 Hz), 110 V 122 W (50/60 Hz), 120 V 140 W (50/60 Hz), 220 V 105 W (50/60 Hz), 230 V 118 W (50/60 Hz), 240 V 130 W (50/60 Hz)			
Temperature range	350-500°C (660-930°F)			
Nozzle to ground resistance	<2 Ω			
Nozzle to ground potential	<2 mV			
Vacuum generator	Diaphragm pump			
Vacuum pressure	81 kPa (610 mmHg)			
Suction flow	11 L/min.			
Standard nozzle	φ1.0 mm (Part No. N50-04)			
Dimensions	210(W)× 226(H)mm / 8.9 x 8.3 in.			
Weight (w/o cord)	0.52 kg (1.1 lb.)			

CA00442LbYa002 2015.3



OVERSEAS AFFILIATES

http://www.HakkoUSA.com

U.S.A.

AMERICAN HAKKO PRODUCTS, INC.
28920 AVE. WILLIAMS VALENCIA, CA 91355, U.S.A.
TEL: (661) 294-0090 FAX: (661) 294-0096
Toll Free (800) 88-HAKKO

HONG KONG
HAKKO DEVELOPMENT CO., LTD.
ROOM 1504, EASTERN HARBOUR CENTRE,
28 HOI CHAK STREET, QUARRY BAY, HONG KONG.
TEL: 2811-5588 FAX: 2590-0217
http://www.hakko.com.hk

TEL:+81-6-6561-3225 FAX:+81-6-6561-8466

http://www.hakko.com E-mail:sales@hakko.com

4-5, SHIOKUSA 2-CHOME, NANIWA-KU, OSAKA, 556-0024 JAPAN

Please access to the following for the other Sales affiliates and distributors. http://www.hakko.com

Specifications and design are subject to change without notice. Copyright HAKKO Corporation. All right reserved.

TBK

TECHNISCHES BÜRO KULLIK GMBH Industriestraße 27 56276 Großmaischeid Tel.: + 49.2689.92770-0

Fax: +49.2689.92770-10 Mail: info@kullik.com Web: www.kullik.com